

## Refine Search

### Search Results -

Terms	Documents
thermal probe calibration	0

Database:

US Pre-Grant Publication Full-Text Database  
 US Patents Full-Text Database  
 US OCR Full-Text Database  
 EPO Abstracts Database  
 JPO Abstracts Database  
 Derwent World Patents Index  
 IBM Technical Disclosure Bulletins

Search:

L44

Refine Search

Recall Text

Clear

Interrupt

### Search History

 DATE: Monday, November 01, 2004    [Printable Copy](#)    [Create Case](#)

#### Set Name Query

side by side

#### Hit Count Set Name

result set

*DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ*

<u>L44</u>	thermal probe calibration	0	<u>L44</u>
<u>L43</u>	tester calibration	111	<u>L43</u>
<u>L42</u>	receptacle tester calibration	0	<u>L42</u>
<u>L41</u>	L39 and "reference"	22	<u>L41</u>
<u>L40</u>	L39 and "reference circuit"	1	<u>L40</u>
<u>L39</u>	receptacle tester	34	<u>L39</u>
<u>L38</u>	outlet tester	27	<u>L38</u>
<u>L37</u>	electrical distribution device tester	0	<u>L37</u>

*DB=USPT; PLUR=YES; OP=ADJ*

<u>L36</u>	4829539.pn.	1	<u>L36</u>
<u>L35</u>	4807083.pn.	1	<u>L35</u>
<u>L34</u>	4743999.pn.	1	<u>L34</u>
<u>L33</u>	4739439.pn.	1	<u>L33</u>
<u>L32</u>	4127837.pn.	1	<u>L32</u>

<u>L31</u>	3890030.pn.	1	<u>L31</u>
<u>L30</u>	3877411.pn.	1	<u>L30</u>
<u>L29</u>	3184726.pn.	1	<u>L29</u>

*DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ*

<u>L28</u>	L26 and "male plug"	29	<u>L28</u>
<u>L27</u>	L26 and "plug"	2267	<u>L27</u>
<u>L26</u>	374/\$	33274	<u>L26</u>
<u>L25</u>	temperature power outlet	0	<u>L25</u>
<u>L24</u>	(power distribution) and (temperature sensor)	1019	<u>L24</u>
<u>L23</u>	(power distribution device) and (temperature sensor)	14	<u>L23</u>
<u>L22</u>	(power distribution box) and (temperature sensor)	7	<u>L22</u>

*DB=USPT; PLUR=YES; OP=ADJ*

BEST AVAILABLE COPY